

Bespoke timber — Architectural signatures

-Timber

—Aluminium—Concrete



I ■ Modinex

The luxurious signature in premium architectural spaces


Welcome to Modinex. We are your design innovation partners. Collaborating with architects and designers to create spaces that delight through bespoke timber architectural signatures.

At Modinex our strength is not just grounded in the unmatched beauty and sustainability of our products, it is our ability to create desire and enhance your designs with luxurious allure.









Our approach

When you specify Modinex, not only do you unlock a stunning array of innovative architectural building products, but you also experience the knowledge of 40+ years of design intelligence and practical ability Modinex has to offer. We inspire unique design opportunities, innovate the products and systems that make them possible and offer after-sales support to bring everything to life with beauty, strength, and compliance. We're passionate about bringing your creative visions to life.

Modinex environmental statement

Modinex recognizes environmental responsibility as a guiding principle in our processes. At Modinex we are dedicated to minimizing the impact on the environment through promoting environmental stewardship, waste, and emission reduction, and by meeting or exceeding environmental laws and regulations.

Using Modinex Long Plank process, we endeavor to utilize our shorter length timber, therefore reducing waste both in the manufacturing process and on the building site. We have fulfilled our "Zero Waste" initiative in our timber manufacturing processes, which is procured from sustainable managed forests, with PEFC Chain of Custody. Modinex strives to continually improve and uphold its environmental performance intentions and advocate sustainability.





Table of Contents

Solid Timber Cladding & Lining

- 4 Beachclad
- 5 Elements Channel Cladding
- 6 Shiplap
- 7 Vee-Joint
- 8 Channel Cladding
- 10 Castelation
- 11 Screenclad
- 12 Stepped Expression
- 13 Diamond & Chamfer
- 14 Rounds
- 15 Flute & Concave
- 16 Convex
- 17 Hex Clad
- 18 Battens & Screening

Solid Timber Species & Finishes

- 19 Timber Species
- 19 Timber Finishes
- 20 Timber Coatings

Aluminium Battens & Cladding

- 22 Alu Selekta Channel
- 23 Alu Selekta Castelation
- 24 Alu Batten

Aluminium Finishes

- 25 Aluminium Timber Grain Finishes
- 26 Solid Powder Coat Colours
- 29 Anodised Colours

Concrete Cladding

30 Viroc





Beachclad

Rustic Weathered Charm


Profiles

120mm wide

170mm wide

18mm thickness available

18mm thickness available



81mm wide

26mm thickness available

26mm thickness available



115mm wide

40mm wide

40mm thickness available

Design — Enhanced weathered character

Features and Benefits

Sustainable timber — Sustainably harvested plantation timber species that is 100%

Variety in timber — Available in four popular profiles in Knotty Grade Western Red

Pre-finished coatings available — Available in a range of standard colours

Application — Suitable for out of weather and external use

Colours









*Custom colours available on request

PROFILE	WESTERN RED CEDAR TIGHT KNOT
BeachClad 120 x 18mm	5.71 kg/m2
BeachClad 170 x 18mm	5.86 kg/m2
BeachClad 115 x 26mm	7.23 kg/m2
BeachClad 81 x 21mm	5.91 kg/m2
BeachClad 81 x 26mm	7.42 kg/m2
BeachClad 40 x 40mm	0.56 kg/lm

Elements Channel Cladding

Timeless Elegance

Profiles



20mm thickness available



40mm thickness available

Colours





*Custom colours available on request







Features and Benefits

Sustainable timber — Sustainably harvested timber species that is 100% PEFC Certified and chemical free

Variety in timber — Available in popular profiles in Thermally Modified Hemlock timber


Pre-finished coatings available — Available in a range of standard colours.

Application — Suitable for out of weather and external use

Durability — High durability for external applications

PROFILE	HEMLOCK THERMALLY MODIFIED
Elements Channel Cladding 120 x 20mm	10.7 kg/m2
Elements Channel Cladding 40 x 40mm	0.90 kg/lm








Shiplap

Profiles



Timber Species and Colours

- Timber species listed on page 19
- Timber coatings listed on page 20

Features and Benefits

Sustainable timber — Available in a range of sustainably certified timber species

Certification — PEFC certified species are available

Easy to install — Concealed fixings for a refined design for ease of installation

Seamless design — Specially designed interlocking tongue allows for secret fixing

Available in both random or set length options

Pre-finished coatings available — Available in a range of standard colours

HEMLOCK WESTERN WESTERN RED CEDAR ALASKAN PROFILE RED CEDAR THERMALLY ACCOYA CEDAR TIGHT KNOT MODIFIED Shiplap 82 x 12mm 3.79 kg/m2 4.98 kg/m2 3.79 kg/m2 5.36 kg/m2 5.54 kg/m2 Shiplap 82 x 15mm 4.57 kg/m2 4.57 kg/m2 6.01 kg/m2 6.47 kg/m2 6.69 kg/m2 Shiplap 82 x 18mm 7.47 kg/m2 5.68 kg/m2 5.68 kg/m2 8.04 kg/m2 8.31 kg/m2 6.05 kg/m2 Shiplap 133 x 15mm 6.51 kg/m2 6.74 kg/m2 4.61 kg/m2 Shiplap 133 x 18mm 5.74 kg/m2 7.54 kg/m2 8.39 kg/m2 8.49 kg/m2 Shiplap 181 x 18mm 5.80 kg/m2 7.63 kg/m2



Minimalistic design

Profiles



Timber Species and Colours

- Timber species listed on page 19

18mm thickness available

- Timber coatings listed on page 20

Features and Benefits

Sustainable timber — Available in a range of sustainably certified timber species

Certification — PEFC certified species are available

Easy to install — Concealed fixings for a refined design for ease of installation


Seamless design — Specially designed interlocking tongue allows for secret fixing

Pre-finished coatings available — Available in a range of standard colours

Application — Options available for external and out of weather applications

PROFILE	WESTERN RED CEDAR	WESTERN RED CEDAR TIGHT KNOT	HEMLOCK THERMALLY MODIFIED	ALASKAN CEDAR	ACCOYA
Vee-joint 86 x 12mm	3.94 kg/m2	3.79 kg/m2	4.98 kg/m2	5.36 kg/m2	5.54 kg/m2
Vee-joint 86 x 15mm	4.78 kg/m2	4.57 kg/m2	6.01 kg/m2	6.47 kg/m2	6.69 kg/m2
Vee-joint 86 x 18mm	5.86 kg/m2	5.68 kg/m2	7.47 kg/m2	8.04 kg/m2	8.31 kg/m2
Vee-joint 133 x 15mm	4.61 kg/m2	4.61 kg/m2	6.05 kg/m2	6.51 kg/m2	6.74 kg/m2
Vee-joint 133 x 18mm	5.74 kg/m2	5.74 kg/m2	7.54 kg/m2	8.11 kg/m2	8.39 kg/m2
Vee-joint 181 x 18mm	5.80 kg/m2	5.80 kg/m2	7.63 kg/m2	8.21kg/m2	8.49 kg/m2







Channel Cladding

Simplistic timeless character

Profiles

4 5

86mm wide

12mm thickness available



70mm wide

18mm thickness available



120mm wide

18mm thickness available



170mm wide

18mm thickness available



115mm wide

26mm thickness available

Features and Benefits

Sustainable timber — Available in a range of sustainably certified timber species

Certification — PEFC certified species are available

Easy to install — Concealed fixings for a refined design for ease of installation

Seamless design — Specially designed interlocking tongue allows for secret fixing

Pre-finished coatings available — Available in a range of standard colours

Application — Options available for external and out of weather applications

Timber Species and Colours

- Timber species listed on page 19

- Timber coatings listed on page 20

PROFILE	WESTERN RED CEDAR	WESTERN RED CEDAR TIGHT KNOT	HEMLOCK THERMALLY MODIFIED	ALASKAN CEDAR	ACCOYA
Channel Cladding 86 x 12mm	3.95 kg/m2	3.95 kg/m2	5.19 kg/m2	5.58 kg/m2	5.78 kg/m2
Channel Cladding 70 x 18mm	5.63 kg/m2	5.63 kg/m2	7.40 kg/m2	7.96 kg/m2	8.23 kg/m2
Channel Cladding 120 x 18mm	5.79 kg/m2	5.79 kg/m2	7.61 kg/m2	8.18 kg/m2	8.47 kg/m2
Channel Cladding 170 x 18mm	5.86 kg/m2	5.86 kg/m2	7.70 kg/m2	8.29 kg/m2	8.57 kg/m2
Channel Cladding 115 x 26mm	5.36 kg/m2	5.36 kg/m2	7.05 kg/m2	7.58 kg/m2	7.84 kg/m2








Castelation

An iconic form of architecture

Profiles



81mm wide

12mm, 18mm thickness availab



81mm wide

21mm and 26mm thickness available

Timber Species and Colours

- Timber species listed on page 19
- Timber coatings listed on page 20

Features and Benefits

Sustainable timber — Available in a range of sustainably certified timber species

Certification — PEFC certified species are available

Easy to install — Concealed fixings for a refined design for ease of installation

Seamless design — Specially designed interlocking tongue allows for secret fixing

Pre-finished coatings available — Available in a range of standard colours

Application — Options available for external and out of weather applications


HEMLOCK ALASKAN WESTERN **PROFILE** RED CEDAR THERMALLY ACCOYA RED CEDAR CEDAR MODIFIED Castelation 81 x 12mm 3.58 kg/m2 4.70 kg/m2 5.06 kg/m2 5.24 kg/m2 Castelation 81 x 18mm 5.30 kg/m2 6.97 kg/m2 7.76 kg/m2 7.77 kg/m2 Castelation 81 x 21mm 5.91 kg/m2 8.64 kg/m2 Castelation 81 x 26mm 7.42 kg/m2 10.86 kg/m2



Screenclad

Natural linear elegance

Profiles



81mm wide

12mm, 18mm thickness available



81mm wide

21mm and 26mm thickness available



20mm wide

21mm, thickness available

Features and Benefits

Sustainable timber — Available in a range of sustainably certified timber species

Certification — PEFC certified species are available

Easy to install — Concealed fixings for a refined design for ease of installation

Seamless design — Specially designed interlocking tongue allows for secret fixing

Pre-finished coatings available — Available in a range of standard colours

Application — Options available for external and out of weather applications

Timber Species and Colours

- Timber species listed on page 19
- Timber coatings listed on page 20

PROFILE	WESTERN RED CEDAR	WESTERN RED CEDAR TIGHT KNOT	HEMLOCK THERMALLY MODIFIED	ALASKAN CEDAR	ACCOYA
Screenclad 81 x 12mm	3.70 kg/m2	3.70 kg/m2	4.86 kg/m2	5.23 kg/m2	5.41 kg/m2
Screenclad 81x 18mm	5.55 kg/m2	5.55 kg/m2	7.29 kg/m2	7.85 kg/m2	8.12 kg/m2
Screenclad 81 x 21mm	6.27 kg/m2	6.27 kg/m2	8.24 kg/m2	8.86 kg/m2	9.17 kg/m2
Screenclad 81 x 26mm	7.91 kg/m2	7.91 kg/m2	10.40 kg/m2	11.19 kg/m2	11.57 kg/m2
Screenclad 120 x 21mm	6.36 kg/m2	6.36 kg/m2	8.36 kg/m2	9.00 kg/m2	9.31 kg/m2







Stepped Expression

17mm thickness Flat series

17mm, 54mm, 81mm, 135mm,

162mm wide available

27mm wide Step series

Profiles



40mm thickness available

26mm thickness available

Features and Benefits

Sustainable timber — Available in a range of sustainably certified timber species

Certification — PEFC certified species are available

Easy to install — Concealed fixings for a refined design for ease of installation

Pre-finished coatings available — Available in a range of standard colours

Application — Options available for external and out of weather applications

Timber Species and Colours

- Timber species listed on page 19
- Timber coatings listed on page 20

PROFILE	WESTERN RED CEDAR	WESTERN RED CEDAR TIGHT KNOT	HEMLOCK THERMALLY MODIFIED	ALASKAN CEDAR	ACCOYA
Stepped Expression Step 27x39mm	0.36 kg/lm	0.36 kg/lm	0.48 kg/lm	0.51 kg/lm	0.53 kg/lm
Stepped Expression Flat 27x17mm	0.15 kg/lm	0.15 kg/lm	0.20 kg/lm	0.21 kg/lm	0.22 kg/lm
Stepped Expression Flat 54x17mm	0.31 kg/lm	0.31 kg/lm	0.40 kg/lm	0.43 kg/lm	0.45 kg/lm
Stepped Expression Flat 81x17mm	0.48 kg/lm	0.48 kg/lm	0.63 kg/lm	0.68 kg/lm	0.71 kg/lm
Stepped Expression Flat 135x17mm	0.77 kg/lm	0.77 kg/lm	1.02 kg/lm	1.10 kg/lm	1.13 kg/lm
Stepped Expression Flat 162x17mm	0.93 kg/lm	0.93 kg/lm	1.22kg/lm	1.32 kg/lm	1.36 kg/lm
Stepped Expression 80x26mm	6.30 kg/m2	6.30 kg/m2	8.28 kg/m2	8.91 kg/m2	9.22 kg/m2
Batten 40x40mm	0.56 kg/lm	0.56 kg/lm	0.74 kg/lm	0.79 kg/lm	0.82 kg/lm



Diamond & Chamfer


Derived from sculptural shapes and forms

Profiles



Diamond Clad Single 81mm wide

26mm thickness available



Diamond Clad Double 81mm wide



Diamond Clad 81mm wide

26mm thickness available



Chamfer Clad 81mm wide

26mm thickness available

Features and Benefits

Sustainable timber — Available in a range of sustainably certified timber species Certification — PEFC certified species are available

Easy to install — Concealed fixings for a refined design for ease of installation Seamless Design — Specially designed interlocking tongue allows for secret fixing

Pre-finished coatings available — Available in a range of standard colours Application — Options available for external and out of weather applications

Timber Species and Colours

- Timber species listed on page 19
- Timber coatings listed on page 20

PROFILE	WESTERN RED CEDAR	WESTERN RED CEDAR TIGHT KNOT	HEMLOCK THERMALLY MODIFIED	ALASKAN CEDAR	ACCOYA
Diamond Clad Single 81 x 26mm	7.57 kg/m2	7.57 kg/m2	9.95 kg/m2	10.71 kg/m2	11.08 kg/m2
Diamond Clad Double 81 x 26mm	7.57 kg/m2	7.57 kg/m2	9.95 kg/m2	10.70 kg/m2	11.07 kg/m2
Diamond Clad 81 x 26mm	7.24 kg/m2	7.24 kg/m2	9.52 kg/m2	10.25 kg/m2	10.60 kg/m2
Chamfered Clad 81 x 26mm	7.19 kg/m2	7.19 kg/m2	9.45 kg/m2	10.17 kg/m2	10.52 kg/m2







Rounds

Embracing biophilic forms

Profiles



Half Dowel 81mm wide 26mm thickness available

Features and Benefits

Sustainable timber — Available in a range of sustainably certified timber species

Certification — PEFC certified species are available

Easy to install — Concealed fixings for a refined design for ease of installation

Seamless design — Specially designed interlocking tongue allows for secret fixing

Pre-finished coatings available — Available in a range of standard colours

Application — Options available for external and out of weather applications

Timber Species and Colours

- Timber species listed on page 19
- Timber coatings listed on page 20


PROFILE	WESTERN RED CEDAR	WESTERN RED CEDAR TIGHT KNOT	HEMLOCK THERMALLY MODIFIED	ALASKAN CEDAR	ACCOYA
Double Round 81 x 26mm	7.28 kg/m2	7.28 kg/m2	9.57 kg/m2	10.29 kg/m2	10.65 kg/m2
Half Dowel 81 x 26mm	7.85 kg/m2	7.85 kg/m2	10.32 kg/m2	11.11 kg/m2	11.49 kg/m2



Flute & Concave

Enhancing spaces through biophilia

Profiles



Single Rib Concave 81x26mm 26mm thickness available

Features and Benefits

Sustainable timber — Available in a range of sustainably certified timber species

Certification — PEFC certified species are available

Easy to install — Concealed fixings for a refined design for ease of installation

Seamless design — Specially designed interlocking tongue allows for secret fixing

Pre-finished coatings available — Available in a range of standard colours

 $\label{lem:application} \textbf{Application} - \textbf{Options} \ \textbf{available} \ \textbf{for external} \ \textbf{and out of weather applications}$

Timber Species and Colours

- Timber species listed on page 19
- Timber coatings listed on page 20

PROFILE	WESTERN RED CEDAR	WESTERN RED CEDAR TIGHT KNOT	HEMLOCK THERMALLY MODIFIED	ALASKAN CEDAR	ACCOYA
Fluted 81 x 26mm	6.71kg/m2	6.71kg/m2	8.82 kg/m2	9.49 kg/m2	9.81 kg/m2
Concave Clad 81 x 26mm	6.43 kg/m2	6.43 kg/m2	8.45 kg/m2	9.09 kg/m2	9.40 kg/m2
Single Rib Concave 81 x 26mm	6.67 kg/m2	6.67 kg/m2	8.77 kg/m2	9.44 kg/m2	9.76 kg/m2







Convex

Sustainable timeless beauty

Profiles



Single Rib Convex 81 x 26 mm

26mm thickness available



Single Rib 81x26mm

26mm thickness available



Ribclad 81x26mm

26mm thickness available

Features and Benefits

Sustainable timber — Available in a range of sustainably certified timber species

Certification — PEFC certified species are available

Easy to install — Concealed fixings for a refined design for ease of installation

Seamless design — Specially designed interlocking tongue allows for secret fixing

Pre-finished coatings available — Available in a range of standard colours

Application — Options available for external and out of weather applications

Timber Species and Colours

- Timber species listed on page 19
- Timber coatings listed on page 20

PROFILE	WESTERN RED CEDAR	WESTERN RED CEDAR TIGHT KNOT	HEMLOCK THERMALLY MODIFIED	ALASKAN CEDAR	ACCOYA
Single Rib Convex 81 x 26mm	7.62 kg/m2	7.62 kg/m2	10.02 kg/m2	10.78 kg/m2	11.15 kg/m2
Single Rib 81 x 26mm	7.35 kg/m2	7.35 kg/m2	9.66 kg/m2	10.39 kg/m2	10.75 kg/m2
Ribclad 81 x 26mm	7.33 kg/m2	7.33 kg/m2	9.63 kg/m2	10.36 kg/m2	10.72 kg/m2



Hex Clad

Imparting a geometric aesthetic

Profiles



Single 81mm wide

26mm thickness available



Double 81mm wide

21mm, 26mm thickness available



Triple 81mm wide

21mm, 26mm thickness availab

Features and Benefits

Sustainable timber — Available in a range of sustainably certified timber species

Certification — PEFC certified species are available

Easy to install — Concealed fixings for a refined design for ease of installation

 $Seamless\,design-Specially\,designed\,interlocking\,tongue\,allows\,for\,secret\,fixing$

Pre-finished coatings available — Available in a range of standard colours

Application — Options available for external and out of weather applications

Timber Species and Colours

- Timber species listed on page 19
- Timber coatings listed on page 20

PROFILE	WESTERN RED CEDAR	WESTERN RED CEDAR TIGHT KNOT	HEMLOCK THERMALLY MODIFIED	ALASKAN CEDAR	ACCOYA
Hex Clad Single 81 x 26mm	7.19 kg/m2	7.19 kg/m2	9.45 kg/m2	10.17 kg/m2	10.52 kg/m2
Hex Clad Double 81 x 21mm	6.00 kg/m2	6.00 kg/m2	7.89 kg/m2	8.49 kg/m2	8.78 kg/m2
Hex Clad Double 81 x 26mm	7.75 kg/m2	7.75 kg/m2	10.19 kg/m2	10.97 kg/m2	11.34 kg/m2
Hex Clad Triple 81 x 21mm	6.44 kg/m2	6.44 kg/m2	8.46 kg/m2	9.10 kg/m2	9.42 kg/m2
Hex Clad Triple 81 x 26mm	8.19 kg/m2	8.19 kg/m2	10.76 kg/m2	11.58 kg/m2	11.98 kg/m2





Battens & Screening

Profiles		Features and Benefits
30mm wide series 30mm, 40mm, thickness available	40mm wide series 40mm, thickness available	Sustainable timber — Available in a range of sustainably certified softwood and hardwood timber species
		Application — Options available for external and out of weather applications Design — A range of surface finishes are available
		Timber Species and Colours
40mm wide x 18mm thick 140mm wide x 18mm	140mm wide x 18mm thick	— Timber species listed on page 19
		— Timber coatings listed on page 20

PROFILE	WESTERN RED CEDAR	WESTERN RED CEDAR TIGHT KNOT	HEMLOCK THERMALLY MODIFIED	ALASKAN CEDAR	ACCOYA
Batten 30 x 30mm	0.32 kg/lm	0.32 kg/lm	0.41 kg/lm	0.45 kg/lm	0.46 kg/lm
Batten 30 x 40mm	0.42 kg/lm	0.42 kg/lm	0.55 kg/lm	0.59 kg/lm	0.61 kg/lm
Batten 40 x 18mm	0.25 kg/lm	0.25 kg/lm	0.33 kg/lm	0.36 kg/lm	0.37 kg/lm
Batten 40 x 40mm	0.56 kg/lm	0.56 kg/lm	0.74 kg/lm	0.79 kg/lm	0.82 kg/lm
Batten 140 x 18mm	0.88 kg/lm	0.88 kg/lm	1.16 kg/lm	1.25 kg/lm	1.29 kg/lm



Timber Species

All our ranges of timber species are available in set length and random length. Please contact our projects team for more information.

-SOFTWOOD

For profiles up to 90mm in width the minimum profile depth is 12mm. Any profile over 90mm in width the minimum depth is 15mm.





Plantation

100% PEFC Certified



100% PEFC Certified



Plantation



Accoya

100% PEFC Certified

Profiles are also available in hardwood timber species such as Blackbutt, Spotted Gum and Ironbark. However due to their m2 weights a commercial garage door will be required.

Timber Finishes

Through to our bespoke in-house manufacturing capabilities, our collection of standard finishes can be customized to meet your design intent. Below is an example of our range of the timber finishes.









Circular Sawn

Band Sawn

Shot Blasted

Dressed

Timber Coatings

Modinex offers a range of finishes to meet our client's design requirements, whilst offering the best protection to our beautiful timber collections.

Penetrating Oil Coatings

Penetrating oils can be used for both internal and external conditions. These oils penetrate the cellular structure of the timber giving it greater protection against UV and weathering. Penetrating oils achieve a natural matt finish.







Please note the above colours are based on the timber species Western Red Cedar. Colour tones may vary depending on species and it is strongly recommend getting a sample of your required timber species and oil colour approved prior

to ordering. For further information about our range of coatings and colours, please contact our projects team hello@modinex.com.au 20 | Modinex Product Catalogue Timber — Aluminium — Concrete





Alu Selekta Channel

Confidence driven by compliance

Profiles



75mm wide

18mm thickness available



155mm wide

18mm thickness available

Finishes and Colours

- Aluminium timber grain colours listed on page 25
- Aluminium plain powder coat colours listed on page 26
- Aluminium Anodised colours listed on page 29

Features and Benefits

Compliance — Code Mark, cyclone & sea salt spray certified

Fire rating — AS1530.1 non-combustible

Durability — 25-year structural & 15-year fading warranty (if plain or timber grain powder coating finish is used)

Availability — Manufactured 100% in Australia with a quick lead time

Easy to install — Concealed fixings for a refined design for ease of installation

Seamless design — Specially design interlocking tongue allows for secret fixing

Sustainability — Available in Green $\,$ Supergreen aluminium to reduce CO2 emission by 50-75%

Design — Available in a range of plain colour or timber grain finishes

Curved design — 75mm wide profile can be curved to a convex radius of 700mm and the 155mm wide profile to a convex radius of 1200mm

PROFILE WEIGHT Alu Selekta Channel 75 x 18mm 9.70 kg/m2 Alu Selekta Channel 155 x 18mm 9.00 kg/m2



Alu Selekta Castelation

Architectural elegance

Profiles



40mm wide

20mm thickness available



160mm wide

20mm thickness available



160mm wide Ultra (lightweight)

20mm thickness available

Finishes and Colours

- Aluminium timber grain colours listed on page 25
- Aluminium plain powder coat colours listed on page 26
- Aluminium Anodised colours listed on page 29

Features and Benefits

Compliance — Code Mark, cyclone & sea salt spray certified

Fire rating — AS1530.1 non-combustible

Durability — 25-year structural & 15-year fading warranty (if plain or timber grain powder coating finish is used)

Availability — Manufactured 100% in Australia with a quick lead time

Easy to install — Concealed fixings for a refined design for ease of installation

Seamless design — Specially design interlocking tongue allows for secret fixing

Sustainability — Available in Green & Supergreen to reduce CO2 emission by 50-75%


Design — Available in a range of plain colour or timber grain finishes


Radius - 40 x 20mm profile is suitable to for convex radius of 300mm or greater

Curved design — 40mm wide profile can be curved to a convex radius of 300mm

PROFILE	WEIGHT
Alu Selekta Castelation 40 x 20mm	17:10 kg/m2
Alu Selekta Castelation 160 x 20mm	11.11 kg/m2
Alu Selekta Castelation Ultra 160 x 20mm	8.49 kg/m2









Alu Batten

Contrived for simplicity

Profiles

25mm series

25mm, 50mm, depth available




40mm series 40mm depth available



50mm series

25mm, 50mm, 75mm, 100mm, 150mm depth available



Features and Benefits

(End caps - Plastic or aluminium end caps available)

Compliance - sea salt spray certified

Fire rating — AS1530.1 non-combustible

Durability — 25-year structural & 15-year fading warranty (if plain or timber grain powder coating finish is used)

Availability - Manufactured 100% in Australia with a guick lead time

Sustainability — Available in Green & Supergreen aluminium to reduce CO2 emission

Design — Available in a range of plain colour or timber grain finishes

Finishes and Colours

- Aluminium timber grain colours listed on page 25
- Aluminium plain powder coat colours listed on page 26
- Aluminium Anodised colours listed on page 29

PROFILE	WEIGHT
Alu Batten 25 x 25mm	0.57 kg/lm
Alu Batten 25 x 50mm	0.78 kg/lm
Alu Batten 40 x 40mm	0.83 kg/lm
Alu Batten 50 x 25mm	0.84 kg/lm
Alu Batten 50 x 50mm	1.06 kg/lm



Aluminium Timber Grain Finishes

-MXDURA

The MX Dura timber look finish is a next-generation signature double baked powder coat timber grain finish with a 3D grain, 25-year structural warranty and 15-year fading warranty for internal and external use.















Spotted Gum

Dark Cedar

American Oak

White Birch











Brown Oak





Dark Smoked Oak

Silvertop Ash







African Ebony

Silver Oak

Solid Powder Coat Colours

*All Interpon or Dulux standard colours are available.

— ALPHA

The Alpha solid colour range is a collection of on trend solid colours, delivered with warranty grade advanced super durable polyester thermosetting powder.





*All Interpon or Dulux standard colours are available.


-CHARISMA

The CharismaTM flat matt range features contemporary, solid colours in a flat matt finish for a subtle and sophisticated look, delivered with warranty grade advanced super durable polyester thermosetting powder.



-STRUTTURA

The Struttura Range is a collection of popular, highly mark and scuff resistant textured finishes built to protect, delivered with warranty grade advanced highly durable polyester thermosetting powder.





*All Interpon or Dulux standard colours are available.

- METTALICO

The Metallico anodised look range is a collection of unique anodised look finishes, designed to subtly change in appearance as light conditions after in the day, delivered with warranty grade advanced super durable polyester thermosetting powder.



Aged Brass

Flat

New Copper

Flat

Burnished Copper



Flat

Flat








Flat





Flat





Medium Bronze

Dark Bronze

Venerable Silver

Flat


Flat



Anodised Colours

-MATT

The traditional sophisticated matt lustre (10% Gloss).













-ILLUSTRO

Best of both, this hybrid provides an elegant look and feel (30% Gloss).







Macchiato - E36TL



Bronze Monument - E30TL






-BRIGHT


A brilliant finish that makes your product stand proud (80% Gloss).



Diamond Light - E87CB














Viroc

Authentic character of concrete



Features and Benefits

Sheet size - 3000mm x 1250mm

Design — Manufactured from Portland Cement, an authentic natural concrete finish

Sustainability — Silica-free and manufactured using 100% recycled PEFC and FSC certified plantation timber

Application — Suitable for internal and external use

Thickness — Available in 12mm thickness

Sealer — If used for flooring, benchtops, splashbacks, or externally a sealer coat is to be applied to protect from staining

Fire rating — Ground 1 internally and BAL29 externally

Finish - Available in a polished or raw finish

Colours











PROFILE

Black

Ochre

WEIGHT 3000 x 1250 x 12mm thick 16.20 kg/m2



Bespoke Timber — Architectural Signatures Modinex Product Catalogue | 31

Timber — Aluminium — Concrete 30 | Modinex Product Catalogue



Custom

At Modinex we're passionate about design. If you are envisioning a particular design or finish that is not listed in this catalogue, reach out to the team at Modinex. What ever your your design is, we can utilise our range of softwood and hardwood timber species and create your bespoke profile to bring your concept through to a reality.

Modinex have a policy of continual improvement to specification. As timber is a natural material and variances in density and moisture content can occur, all weights are approximations and need to be considered with a tolerance of +/-15%. Product colours, grades, finishes and sizes may change without notice. Due to printing restraints, actual colours, grades, and finishes may vary from what is shown in this brochure. All information is current at the time of publishing this brochure. Please check our website for updated information and standards. June 2024 Publication.

